



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

1 Identification

· **Product identifier**

· **Trade name:** Signum zirconia bond I

· **Application of the substance / the mixture** Zirconia-Resin Bonding System

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Information department:**

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545

e-mail: customer.servicehkna@kulzer-dental.com

· **Emergency telephone number:**

Emergency CONTACT (24-Hour-Number)

GBK/Infotrac ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

· **Classification of the substance or mixture**

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.

Skin Irritation - Category 2

H315 Causes skin irritation.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure -
Category 3

H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

acetone

· **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

CDN



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum zirconia bond I

(Contd. of page 1)

Specific treatment (see on this label).
Store locked up.

Hazard description:

Canadian Hazard Symbols

B2 - Flammable liquid
D2B - Toxic material causing other toxic effects



Classification system

NFPA ratings for USA (scale 0-4)



Health = 1
Fire = 3
Reactivity = 0

HMIS-Ratings (Scale 0-4)



Health = 1
Fire = 3
Reactivity = 0

Other hazards -

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: -

Dangerous components:

67-64-1	acetone Flammable Liquids - Category 2, H225; Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	>90% w/w
64-19-7	acetic acid Flammable Liquids - Category 3, H226; Skin Corrosion - Category 1A, H314	<1% w/w

Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

Description of first aid measures

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum zirconia bond I

(Contd. of page 2)

- **After swallowing**
*Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.*
- **Information for doctor**
 - **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 - **For safety reasons unsuitable extinguishing agents** *Water with full jet.*
- **Special hazards arising from the substance or mixture**
*Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.*
- **Advice for firefighters**
 - **Protective equipment:**
*Wear self-contained respiratory protective device.
Wear fully protective suit.*
- **Additional information -**

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** *Prevent seepage into sewage system, workpits and cellars.*
- **Methods and material for containment and cleaning up:**
*Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).
Ensure adequate ventilation.
Send for recovery or disposal in suitable receptacles.*
- **Reference to other sections**
*See Section 13 for disposal information.
See Section 8 for information on personal protection equipment.*
-

7 Handling and storage

- **Handling**
 - **Precautions for safe handling**
*Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.*
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum zirconia bond I

Protect against electrostatic charges.

(Contd. of page 3)

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

EL () Short-term value: 500 ppm
Long-term value: 250 ppm

EV () Short-term value: 750 ppm
Long-term value: 500 ppm

64-19-7 acetic acid

EL () Short-term value: 15 ppm
Long-term value: 10 ppm

EV () Short-term value: 37 mg/m³, 15 ppm
Long-term value: 25 mg/m³, 10 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.
recommended

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance

(Contd. on page 5)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum zirconia bond I

(Contd. of page 4)

- and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
Butyl rubber, BR
Nitrile rubber, NBR
- **Eye protection:** Safety glasses
- **Body protection:** Protective work clothing.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- **Form:** Fluid
- **Color:** Colorless
- **Odor:** Acetone-like
- **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

- **Melting point/Melting range:** undetermined
- **Boiling point/Boiling range:** 55 °C (131 °F)

· **Flash point:** -19 °C (-2 °F)

· **Flammability (solid, gaseous)** Not applicable.

· **Ignition temperature:** 465 °C (869 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

- **Lower:** 2.6 Vol %
- **Upper:** 13.0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 247 hPa (185 mm Hg)

· **Density:**

- **Relative density** Not determined.
- **Vapor density** Not determined.
- **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

- **Water:** Not miscible or difficult to mix

(Contd. on page 6)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum zirconia bond I

(Contd. of page 5)

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· **dynamic:**

Not determined.

· **kinematic:**

Not determined.

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** none
- **Additional information:** -

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral LD50 5800 mg/kg (rat)

Dermal LD50 20000 mg/kg (rabbit)

64-19-7 acetic acid

Oral LD50 3310 mg/kg (rat)

Dermal LD50 1060 mg/kg (can)

· **Primary irritant effect:**

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Subacute to chronic toxicity:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· **Additional toxicological information:** Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

Butyl-hydroxy-toluol

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

CDN

(Contd. on page 7)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum zirconia bond I

(Contd. of page 6)

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

67-64-1 acetone

EC50/48h 6100 mg/l (daphnia)

LC50/96h 5540 mg/l (fish)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT**

UN1090

· **TDG, IMDG, IATA**

1090

· **UN proper shipping name**

· **TDG**

1090 ACETONE, solution

· **IMDG, IATA**

ACETONE, solution

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

(Contd. on page 8)





Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum zirconia bond I

(Contd. of page 7)

· Label	3
· TDG (Transport dangerous goods):	
	
· Class	3 (F1) Flammable liquids
· Label	3
<hr/>	
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, TDG, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	-
· UN "Model Regulation":	UN1090, Acetone, solution, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02



GHS07

(Contd. on page 9)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum zirconia bond I

(Contd. of page 8)

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
acetone
- **Hazard statements**
Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
- **Precautionary statements**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use explosion-proof [electrical/ventilating/lighting] equipment.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
Store locked up.
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H314 Causes severe skin burns and eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Date of preparation / last revision** *06/03/2017 / 2*
- **Abbreviations and acronyms:**
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
- *** Data compared to the previous version altered.**