



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: Signum ceramic bond I**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Auxiliary for manufacture of dental prothesis

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Informing department:** E-Mail: msds@kulzer-dental.com

· **1.4 Emergency telephone number:** Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

propan-2-ol

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

· **2.3 Other hazards -**

(Contd. on page 2)

GB



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

Trade name: Signum ceramic bond I

- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** -

· **Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	75-90%
CAS: 67-64-1 EINECS: 200-662-2	acetone	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5-10%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** The product is not skin irritating.
- **After eye contact**
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
In case of persistent symptoms consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents**

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

- **Protective equipment:** No special measures required.
- **Additional information** -

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

Trade name: Signum ceramic bond I

(Contd. of page 2)

- **6.2 Environmental precautions:**
Prevent material from reaching sewage system, holes and cellars.
Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
No dangerous materials are released.
See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep containers tightly sealed.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage**
 - **Requirements to be met by storerooms and containers:** Store in cool location.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Store in cool, dry conditions in well sealed containers.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

· **8.1 Control parameters**

- **Components with critical values that require monitoring at the workplace:**

67-63-0 propan-2-ol

OES () Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

67-64-1 acetone

OES () Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm
New, IOELV

· **DNELs**

67-64-1 acetone

Oral	ge.pop., l.te, syst.	62 mg/Kg (nd)
Dermal	worker profess., acute, syst.	2420 mg/Kg/d (nd)
	worker profess., l.te., syst.	186 mg/Kg/d (nd)
Inhalative	ge.pop., l.te, syst.	62 mg/Kg/d (nd)
	worker profess., l.te., syst.	1210 mg/m ³ (nd)

(Contd. on page 4)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

Trade name: Signum ceramic bond I

(Contd. of page 3)

ge.pop., l.te, syst.	200 mg/m3 (nd)
----------------------	----------------

· PNECs

67-64-1 acetone

freshwater	10.6 mg/l (nd)
marine water	1.06 mg/l (rabbit)
STP	19.5 mg/l (nd)
sedim., dw, fre.wat.	30.4 mg/Kg (nd)
sedim., dw, mar.wat.	3.04 mg/Kg (nd)
soil,dw	0.112 mg/Kg (nd)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Avoid contact with the eyes.
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.

· Breathing equipment:

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Check protective gloves prior to each use for their proper condition.
recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR
Nitrile rubber, NBR

· Eye protection:

Protective goggles are recommended.
Tightly sealed safety glasses.

· Body protection: Light weight protective clothing

GB

(Contd. on page 5)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

Trade name: Signum ceramic bond I

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· **Form:** Fluid

· **Colour:** Colourless

· **Smell:** Alcohol-like

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· Change in condition

· **Melting point/Melting range:** Not determined

· **Boiling point/Boiling range:** 55 °C

· **Flash point:** 5 °C

· **Inflammability (solid, gaseous)** Not applicable.

· **Ignition temperature:** >400 °C

· **Decomposition temperature:** Not determined.

· **Self-inflammability:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures is possible.

· Critical values for explosion:

· **Lower:** 2.0 Vol %

· **Upper:** 12.0 Vol %

· **Steam pressure at 20 °C:** 48 hPa

· **Density at 20 °C** 0.800 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· Solubility in / Miscibility with

· **Water:** Fully miscible

· **Partition coefficient (n-octanol/water):** Not determined.

· Viscosity:

· **dynamic:** Not determined.

· **kinematic:** Not determined.

· Solvent content:

· **Water:** 4.0 %

· **VOC EU** 769.7 g/l

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

(Contd. on page 6)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

Trade name: Signum ceramic bond I

(Contd. of page 5)

- **10.2 Chemical stability**
 - **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

67-63-0 propan-2-ol

Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
 - **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
 - **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
 - **Carcinogenicity** Based on available data, the classification criteria are not met.
 - **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**

· **Aquatic toxicity:**

67-63-0 propan-2-ol

EC50/72h	>1000 mg/l (algae)
EC50/48h	13299 mg/l (daphnia)
LC50/96h	1400 mg/l (fish)

67-64-1 acetone

EC50/48h	6100 mg/l (daphnia)
LC50/96h	5540 mg/l (fish)

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

Trade name: Signum ceramic bond I

(Contd. of page 6)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
 - **Additional ecological information:**
 - **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.


SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - **Waste disposal key number:** 55503
- **European waste catalogue**

18 01 06	chemicals consisting of or containing dangerous substances
----------	--
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.
 - **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

- **14.1 UN-Number**
 - **ADR, IMDG, IATA** UN1993
- **14.2 UN proper shipping name**
 - **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (vapor pressure at 50 °C at most 110 kPa) (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE)
 - **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE)
- **14.3 Transport hazard class(es)**
 - **ADR**



· **Class** 3 (F1) Flammable liquids.

(Contd. on page 8)



Safety data sheet
according to 1907/2006/EC, Article 31


Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

Trade name: Signum ceramic bond I

(Contd. of page 7)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number:	33
· EMS Number:	F-E, <u>S-E</u>
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	-
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D/E
· UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S., 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

Trade name: Signum ceramic bond I

(Contd. of page 8)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
* **Data compared to the previous version altered.**

GB