



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

1 Identification

· **Product identifier**

· **Trade name:** Palavit G Liquid

· **Application of the substance / the mixture** Manufacture of dental prothesis

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Information department:**

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545

e-mail: customer.servicehkna@kulzer-dental.com

· **Emergency telephone number:**

Emergency CONTACT (24-Hour-Number)

GBK/Infotrac ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

· **Classification of the substance or mixture**

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.

Skin Irritation - Category 2

H315 Causes skin irritation.

Skin Sensitizer - Category 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure -
Category 3

H335 May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure -
Category 2

H373 May cause damage to organs through
prolonged or repeated exposure.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

methyl methacrylate

N,N-dimethyl-p-toluidine

· **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. on page 2)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Palavit G Liquid

(Contd. of page 1)

Do not breathe dust/fume/gas/mist/vapours/spray.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
Specific treatment (see on this label).
Store locked up.

· **Hazard description:**

· **Canadian Hazard Symbols**

- B2 - Flammable liquid
- D2B - Toxic material causing other toxic effects



· **Classification system**

· **NFPA ratings for USA (scale 0-4)**



Health = 1
Fire = 3
Reactivity = 0

· **HMIS-Ratings (Scale 0-4)**



HEALTH 1 Health = 1
FIRE 3 Fire = 3
REACTIVITY 0 Reactivity = 0

· **Other hazards -**

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description: -**

· **Dangerous components:**

80-62-6	methyl methacrylate	>90% w/w
Flammable Liquids - Category 2, H225; Skin Irritation - Category 2, H315; Skin Sensitizer - Category 1, H317; Specific Target Organ Toxicity - Single Exposure - Category 3, H335		

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **General information**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact** If skin irritation continues, consult a doctor.
- **After eye contact** Rinse opened eye for several minutes under running water.

(Contd. on page 3)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Palavit G Liquid

(Contd. of page 2)

- **After swallowing**
Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.
- **Information for doctor** Composition based on methacrylates
 - **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.
 - **For safety reasons unsuitable extinguishing agents** Water.
- **Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
 - **Protective equipment:**
Wear self-contained respiratory protective device.
Mount respiratory protective device.
- **Additional information** -

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
No dangerous substances are released.
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
-

7 Handling and storage

- **Handling**
 - **Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Palavit G Liquid

(Contd. of page 3)

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**
- **Storage**
 - **Requirements to be met by storerooms and receptacles:** Store in a cool location.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

80-62-6 methyl methacrylate

EL () Short-term value: 100 ppm
Long-term value: 50 ppm
S

EV () Short-term value: 100 ppm
Long-term value: 50 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
 - **Personal protective equipment**
 - **General protective and hygienic measures**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
 - **Breathing equipment:**
Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).
 - **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.
Solvent resistant gloves
Check protective gloves prior to each use for their proper condition.
recommended
 - **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Palavit G Liquid

(Contd. of page 4)

- **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 30 minutes (Permeation according to EN 374 Part 3: Level 2).
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
Butyl rubber, BR
Nitrile rubber, NBR
- **Eye protection:** Safety glasses
- **Body protection:** Light weight protective clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
· Form:	Fluid
· Color:	Colorless
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/Melting range:	-48 °C (-54 °F)
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	10 °C (50 °F)
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	430 °C (806 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	2.1 Vol %
· Upper:	12.5 Vol %
· Vapor pressure at 20 °C (68 °F):	47 hPa (35 mm Hg)
· Density at 20 °C (68 °F):	
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.

(Contd. on page 6)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Palavit G Liquid

(Contd. of page 5)

· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix
· Partition coefficient (n-octanol/water) at 20 °C (68 °F):	1.38 log POW
· Viscosity:	
· dynamic:	Not determined.
· kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Possibility of hazardous reactions** Exothermic polymerization
- **Conditions to avoid** Heat, flames and sparks.
- **Incompatible materials:**
Reacts with reducing agents
Reacts with heavy metals
Reacts with peroxides and other radical forming substances
- **Hazardous decomposition products:** none
- **Additional information:** -

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
80-62-6 methyl methacrylate		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat)
99-97-8 N,N-dimethyl-p-toluidine		
Inhalative	LC50/4 h	1400 mg/l (rat)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** No data available.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
Irritant
Harmful

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)	
80-62-6	methyl methacrylate

3

(Contd. on page 7)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Palavit G Liquid

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

99-97-8 N,N-dimethyl-p-toluidine

LC50/96h 100 mg/l (fish)

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Disposal must be made according to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, TDG, IMDG, IATA

UN1247

· UN proper shipping name

· DOT

METHYL METHACRYLATE MONOMER, STABILIZED, solution

· TDG

1247 METHYL METHACRYLATE MONOMER, STABILIZED, solution

· IMDG

METHYL METHACRYLATE MONOMER, STABILIZED solution

· IATA

Methyl methacrylate monomer, stabilized solution

(Contd. on page 8)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Palavit G Liquid

(Contd. of page 7)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
· **Label** 3

· **TDG (Transport dangerous goods):**



· **Class** 3 (F1) Flammable liquids
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids
· **Label** 3

· **Packing group**

· **DOT, TDG, IMDG, IATA** II

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):** 339

· **EMS Number:** F-E,S-D

· **Stowage Category** B

· **Stowage Code** SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

-

· **TDG**

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Palavit G Liquid

(Contd. of page 8)

· **IMDG**

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

1L

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN1247, METHYL METHACRYLATE MONOMER, STABILIZED, solution, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **SARA Section 355 (extremely hazardous substances)**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act)** None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

methyl methacrylate

N,N-dimethyl-p-toluidine

- **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Specific treatment (see on this label).

Store locked up.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

CDN

(Contd. on page 10)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Palavit G Liquid

(Contd. of page 9)

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H225 Highly flammable liquid and vapour.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H335 May cause respiratory irritation.
- **Date of preparation / last revision** 06/03/2017 / 2
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - WHMIS: Workplace Hazardous Materials Information System (Canada)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
- *** Data compared to the previous version altered.**