



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· Trade name: **Palavit G Liquid**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.

· **Application of the substance / the mixture** Manufacture of dental prosthesis

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Informing department:** E-Mail: [msds@kulzer-dental.com](mailto:msds@kulzer-dental.com)

· **1.4 Emergency telephone number:** Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

methyl methacrylate

N,N-dimethyl-p-toluidine

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P243 Take precautionary measures against static discharge.

P370+P378 In case of fire: Use for extinction: CO2, sand, extinguishing powder.

P403 Store in a well-ventilated place.

(Contd. on page 2)

IRL



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

**Trade name: Palavit G Liquid**

(Contd. of page 1)

- **2.3 Other hazards -**
- **Results of PBT and vPvB assessment**
  - **PBT:** Not applicable.
  - **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

- **3.2 Chemical characterisation: Mixtures**
- **Description:** -

· **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-0000	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	> 90%
CAS: 99-97-8 EINECS: 202-805-4	N,N-dimethyl-p-toluidine Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Chronic 3, H412	0-5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
  - **General information**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
  - **After inhalation** Supply fresh air; consult doctor in case of symptoms.
  - **After skin contact** If skin irritation continues, consult a doctor.
  - **After eye contact** Rinse opened eye for several minutes under running water.
  - **After swallowing**  
Rinse out mouth and then drink plenty of water.  
In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
  - **Information for doctor** Product based on methacrylates
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
  - **Suitable extinguishing agents** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
  - **For safety reasons unsuitable extinguishing agents** Water.
- **5.2 Special hazards arising from the substance or mixture**  
Can form explosive gas-air mixtures.  
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
  - **Protective equipment:**  
Wear self-contained breathing apparatus.

(Contd. on page 3)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

**Trade name: Palavit G Liquid**

Put on breathing apparatus.  
· **Additional information** -

(Contd. of page 2)

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).  
Dispose of contaminated material as waste according to item 13.
- **6.4 Reference to other sections**  
No dangerous materials are released.  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep containers tightly sealed.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
  - **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
  - **Storage**
    - **Requirements to be met by storerooms and containers:** Store in cool location.
    - **Information about storage in one common storage facility:** Not required.
    - **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed containers.
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **8.1 Control parameters**

· <b>Components with critical values that require monitoring at the workplace:</b>	
<b>80-62-6 methyl methacrylate</b>	
OEL ( )	Short-term value: 100 ppm Long-term value: 50 ppm

(Contd. on page 4)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

**Trade name: Palavit G Liquid**

(Contd. of page 3)

**· DNELs**

**80-62-6 methyl methacrylate**

Dermal	worker industr., l.te., syst.	74.3 mg/Kg/d (human)
Inhalative	worker industr., l.te., syst.	210 mg/m <sup>3</sup> (human)

**· PNECs**

**80-62-6 methyl methacrylate**

freshwater	0.94 mg/l (aqua)
------------	------------------

**· Additional information:** The lists that were valid during the compilation were used as basis.

**· 8.2 Exposure controls**

**· Personal protective equipment**

**· General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.  
Instantly remove any soiled and impregnated garments.  
Wash hands during breaks and at the end of the work.  
Avoid contact with the eyes and skin.

**· Breathing equipment:**

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

**· Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

recommended

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 30 minutes (Permeation according to EN 374 Part 3: Level 2).

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber, BR

Nitrile rubber, NBR

**· Eye protection:** Safety glasses

**· Body protection:** Light weight protective clothing

IRL

(Contd. on page 5)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

**Trade name: Palavit G Liquid**

(Contd. of page 4)

**SECTION 9: Physical and chemical properties**

**· 9.1 Information on basic physical and chemical properties**

**· General Information**

**· Appearance:**

· **Form:**

Fluid

· **Colour:**

Colourless

· **Smell:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

**· Change in condition**

· **Melting point/Melting range:**

-48 °C

· **Boiling point/Boiling range:**

100 °C

· **Flash point:**

10 °C

· **Inflammability (solid, gaseous)**

Not applicable.

· **Ignition temperature:**

430 °C

· **Decomposition temperature:**

Not determined.

· **Self-inflammability:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapour mixtures is possible.

· **Critical values for explosion:**

· **Lower:**

2.1 Vol %

· **Upper:**

12.5 Vol %

· **Steam pressure at 20 °C:**

47 hPa

· **Density at 20 °C**

0.94 g/cm<sup>3</sup>

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**

· **Water:**

Not miscible or difficult to mix

· **Partition coefficient (n-octanol/water) at 20 °C:** 1.38 log POW

· **Viscosity:**

· **dynamic:**

Not determined.

· **kinematic:**

Not determined.

· **9.2 Other information**

No further relevant information available.

**SECTION 10: Stability and reactivity**

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** Exothermic polymerisation

(Contd. on page 6)

IRL



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

**Trade name: Palavit G Liquid**

(Contd. of page 5)

- **10.4 Conditions to avoid** Heat, flames and sparks.
- **10.5 Incompatible materials:**
  - Reacts with reducing agents
  - Reacts with heavy metals
  - Reacts with peroxides and other radical forming substances
- **10.6 Hazardous decomposition products:** None
  - **Additional information:** -

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
  - **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**80-62-6 methyl methacrylate**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat)

**99-97-8 N,N-dimethyl-p-toluidine**

Inhalative	LC50/4 h	1400 mg/l (rat)
------------	----------	-----------------

- **Primary irritant effect:**
  - **Skin corrosion/irritation** Causes skin irritation.
  - **Serious eye damage/irritation** No data available.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
  - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
  - **Carcinogenicity** Based on available data, the classification criteria are not met.
  - **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

- **12.1 Toxicity**

· **Aquatic toxicity:**

**99-97-8 N,N-dimethyl-p-toluidine**

LC50/96h	100 mg/l (fish)
----------	-----------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 7)





**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

**Trade name: Palavit G Liquid**

(Contd. of page 6)


- *Danger to drinking water if even small quantities leak into soil.*
- **12.5 Results of PBT and vPvB assessment**
  - **PBT:** Not applicable.
  - **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
  - **Recommendation**  
Disposal must be made according to official regulations.  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
  - **Uncleaned packagings:**
    - **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**


- **14.1 UN-Number**
  - **ADR, IMDG, IATA** UN1247
- **14.2 UN proper shipping name**
  - **ADR** 1247 METHYL METHACRYLATE MONOMER, STABILIZED, solution
  - **IMDG** METHYL METHACRYLATE MONOMER, STABILIZED solution
  - **IATA** Methyl methacrylate monomer, stabilized solution
- **14.3 Transport hazard class(es)**
  - **ADR**



- **Class** 3 (F1) Flammable liquids.
    - **Label** 3

---

  - **IMDG, IATA**



- **Class** 3 Flammable liquids.
    - **Label** 3

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

**Trade name: Palavit G Liquid**

(Contd. of page 7)

· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	II
· <b>14.5 Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b> · <b>Kemler Number:</b> · <b>EMS Number:</b> · <b>Stowage Category</b> · <b>Stowage Code</b>	Warning: Flammable liquids. 339 F-E,S-D B SW2 Clear of living quarters.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	-
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>Transport category</b> · <b>Tunnel restriction code</b>	2 D/E
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN1247, METHYL METHACRYLATE MONOMER, STABILIZED, solution, 3, II

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
  - **Directive 2012/18/EU**
    - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
    - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
    - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

IRL

(Contd. on page 9)





**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.06.2017

Version number 3

Revision: 03.06.2017

**Trade name: Palavit G Liquid**

(Contd. of page 8)

**SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Acute Tox. 3: Acute toxicity – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- \* **Data compared to the previous version altered.**