



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 11.09.2017

Version number 3

Revision: 11.09.2017

Hazardous according to criteria of Australian Safety and Compensation Council

**1 Identification of the substance/mixture and of the company/undertaking**

· **Product identifier**

· **Trade name:** **iBOND Ceramic Primer**

· **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.

· **Application of the substance / the mixture** Auxiliary for manufacture of dental prothesis

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Heraeus Kulzer Australia Pty Ltd  
Unit 32  
11 – 21 Underwood Rd  
HOMEBUSH NSW 2140  
Australia

Tel: +61 (0) 2 9764 5222

· **Informing department:** see above

· **Emergency telephone number:** Emergency contact number: 13 11 26 (24 hours)

**2 Hazards identification**

· **Classification of the substance or mixture**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard statements**

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

· **Other hazards -**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 2)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 11.09.2017

Version number 3

Revision: 11.09.2017

**Trade name: iBOND Ceramic Primer**

· **vPvB:** Not applicable.

(Contd. of page 1)

### 3 Composition/information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:** -

· **Dangerous components:**

CAS: 67-63-0	propan-2-ol	75-90%
EINECS: 200-661-7	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 67-64-1	acetone	5-10%
EINECS: 200-662-2	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

### 4 First aid measures

· **Description of first aid measures**

· **After inhalation** Supply fresh air; consult doctor in case of symptoms.

· **After skin contact** The product is not skin irritating.

· **After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· **After swallowing**

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents**

CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

· **Additional information** -

### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Ensure adequate ventilation.

(Contd. on page 3)

AUS



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 11.09.2017

Version number 3

Revision: 11.09.2017

**Trade name: iBOND Ceramic Primer**

(Contd. of page 2)

- **Reference to other sections**  
No dangerous materials are released.  
See Section 8 for information on personal protection equipment.

**7 Handling and storage**

- **Handling**
  - **Precautions for safe handling** Keep containers tightly sealed.
  - **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
  - **Storage**
    - **Requirements to be met by storerooms and containers:** Store in cool location.
    - **Information about storage in one common storage facility:** Not required.
    - **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed containers.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

**67-63-0 propan-2-ol**

NES (Australia)	Short-term value: 1230 mg/m <sup>3</sup> , 500 ppm Long-term value: 983 mg/m <sup>3</sup> , 400 ppm
PEL (USA)	980 mg/m <sup>3</sup> , 400 ppm
REL (USA)	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV (USA)	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm

**67-64-1 acetone**

PEL (USA)	2400 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	590 mg/m <sup>3</sup> , 250 ppm
TLV (USA)	Short-term value: 1782 mg/m <sup>3</sup> , 750 ppm Long-term value: 1188 mg/m <sup>3</sup> , 500 ppm BEI

· **DNELs**

**67-64-1 acetone**

Oral	ge.pop., l.te, syst.	62 mg/Kg (nd)
Dermal	worker profess., acute, syst.	2420 mg/Kg/d (nd)
	worker profess., l.te., syst.	186 mg/Kg/d (nd)
Inhalative	ge.pop., l.te, syst.	62 mg/Kg/d (nd)
	worker profess., l.te., syst.	1210 mg/m <sup>3</sup> (nd)
	ge.pop., l.te, syst.	200 mg/m <sup>3</sup> (nd)

(Contd. on page 4)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 11.09.2017

Version number 3

Revision: 11.09.2017

**Trade name: iBOND Ceramic Primer**

(Contd. of page 3)

· PNECs	
<b>67-64-1 acetone</b>	
freshwater	10.6 mg/l (nd)
marine water	1.06 mg/l (rabbit)
STP	19.5 mg/l (nd)
sedim., dw, fre.wat.	30.4 mg/Kg (nd)
sedim., dw, mar.wat.	3.04 mg/Kg (nd)
soil,dw	0.112 mg/Kg (nd)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

- Avoid contact with the eyes.
- Keep away from foodstuffs, beverages and food.
- Instantly remove any soiled and impregnated garments.
- Wash hands during breaks and at the end of the work.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
Check protective gloves prior to each use for their proper condition.  
recommended

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

- Butyl rubber, BR
- Nitrile rubber, NBR

· **Eye protection:**

Protective goggles are recommended.  
Tightly sealed safety glasses.

· **Body protection:** Light weight protective clothing

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- **Form:** Fluid
- **Colour:** Colourless

(Contd. on page 5)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 11.09.2017

Version number 3

Revision: 11.09.2017

**Trade name: iBOND Ceramic Primer**

(Contd. of page 4)

· <b>Smell:</b>	Alcohol-like
· <b>Odour threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
· <b>Melting point/Melting range:</b>	Not determined
· <b>Boiling point/Boiling range:</b>	55 °C
· <b>Flash point:</b>	5 °C
· <b>Inflammability (solid, gaseous)</b>	Not applicable.
· <b>Ignition temperature:</b>	>400 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures is possible.
· <b>Critical values for explosion:</b>	
· <b>Lower:</b>	2.0 Vol %
· <b>Upper:</b>	12.0 Vol %
· <b>Steam pressure at 20 °C:</b>	48 hPa
· <b>Density at 20 °C</b>	0.800 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with</b>	
· <b>Water:</b>	Fully miscible
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
· <b>dynamic:</b>	Not determined.
· <b>kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
· <b>Water:</b>	4.0 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
  - **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** None

AUS

(Contd. on page 6)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 11.09.2017

Version number 3

Revision: 11.09.2017

**Trade name: iBOND Ceramic Primer**

(Contd. of page 5)

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values that are relevant for classification:**

**67-63-0 propan-2-ol**

Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

**67-64-1 acetone**

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Irritant effect.
- **Respiratory or skin sensitisation** No sensitizing effect known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:  
Irritant

**12 Ecological information**

- **Toxicity**

- **Aquatic toxicity:**

**67-63-0 propan-2-ol**

EC50/72h	>1000 mg/l (algae)
EC50/48h	13299 mg/l (daphnia)
LC50/96h	1400 mg/l (fish)

**67-64-1 acetone**

EC50/48h	6100 mg/l (daphnia)
LC50/96h	5540 mg/l (fish)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

AUS

(Contd. on page 7)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.09.2017

Version number 3

Revision: 11.09.2017



**Trade name: iBOND Ceramic Primer**

(Contd. of page 6)

**13 Disposal considerations**

- **Waste treatment methods**
  - **Recommendation**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
  - **Recommendation:** Disposal must be made according to official regulations.
  - **Recommended cleaning agent:** Water, if necessary with cleaning agent.

**14 Transport information**

· <b>UN-Number</b> · <b>ADG, IMDG, IATA</b>	UN1993
· <b>UN proper shipping name</b> · <b>ADG</b>	1993 FLAMMABLE LIQUID, N.O.S. (vapor pressure at 50 °C at most 110 kPa) (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE)
· <b>IMDG, IATA</b>	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE)
· <b>Transport hazard class(es)</b> · <b>ADG</b>	
	
· <b>Class</b> · <b>Label</b>	3 (F1) Flammable liquids. 3
· <b>IMDG, IATA</b>	
	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids. 3
· <b>Packing group</b> · <b>ADG, IMDG, IATA</b>	II
· <b>Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b> · <b>Kemler Number:</b> · <b>EMS Number:</b>	Warning: Flammable liquids. 33 F-E, S-E
· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	-

(Contd. on page 8)





**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 11.09.2017

Version number 3

Revision: 11.09.2017

**Trade name: iBOND Ceramic Primer**

(Contd. of page 7)

· **ADG**

- |                                  |     |
|----------------------------------|-----|
| · <b>Limited quantities (LQ)</b> | 1L  |
| · <b>Transport category</b>      | 2   |
| · <b>Tunnel restriction code</b> | D/E |

- **UN "Model Regulation":** UN1993, FLAMMABLE LIQUID, N.O.S., special provision 640D (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE), 3, II

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard statements**

Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

(Contd. on page 9)





**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 11.09.2017

Version number 3

Revision: 11.09.2017

**Trade name: iBOND Ceramic Primer**

(Contd. of page 8)

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

· **\* Data compared to the previous version altered.**

AUS