



**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 08/10/2021

Reviewed on 08/10/2021

## 1 Identification

· **Product identifier**

· **Trade name:** **iBOND Total Etch**

· -

· **Application of the substance / the mixture** Dental bonding material

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Information department:**

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545

e-mail: [customer.servicehkna@kulzer-dental.com](mailto:customer.servicehkna@kulzer-dental.com)

· **Emergency telephone number:**

Emergency CONTACT (24-Hour-Number)

ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

## 2 Hazard(s) identification

· **Classification of the substance or mixture**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate

glutaral

2-hydroxyethyl methacrylate

4-methacryloxyethyltrimellitic acid anhydride

· **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

· **Precautionary statements**

Avoid breathing mist/vapours/spray.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**

(Contd. of page 1)

If skin irritation or rash occurs: Get medical advice/attention.  
If experiencing respiratory symptoms: Call a poison center/doctor.

**Classification system**

**NFPA ratings for USA (scale 0-4)**



**HMIS-Ratings (Scale 0-4)**



**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**

**Chemical characterization: Mixtures**

**Description:** -

**Dangerous components:**

64-17-5	ethanol Flam. Liq. 2, H225 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	≥25-<50%
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate Skin Sens. 1B, H317	≥25-≤50%
868-77-9	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	≥10-≤25%
	Poly(methacrylic-oligo-acrylic acid) Eye Irrit. 2A, H319	0-5%
70293-55-9	4-methacryloxyethyltrimellitic acid anhydride Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	≥1-<5%
111-30-8	glutaral Acute Tox. 3, H301; Acute Tox. 2, H330 Resp. Sens. 1, H334 Skin Corr. 1B, H314 Skin Sens. 1A, H317; STOT SE 3, H335 Flam. Liq. 4, H227 Specific concentration limit: STOT SE 3; H335: C ≥ 0.5 %	≥1-<5%

**Additional information** For the wording of the listed hazard phrases refer to section 16.

**4 First-aid measures**

**Description of first aid measures**

- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact**  
Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)



**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**

(Contd. of page 2)

- **After swallowing**  
If symptoms persist consult doctor.  
Rinse out mouth and then drink plenty of water.  
Immediately call a doctor.
- **Information for doctor**
  - **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
  - **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
  - **Suitable extinguishing agents**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
  - **For safety reasons unsuitable extinguishing agents** Water with full jet.
- **Special hazards arising from the substance or mixture**  
Can form explosive gas-air mixtures.  
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
  - **Protective equipment:** Mount respiratory protective device.
- **Additional information -**

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow to penetrate the ground/soil.  
No special measures required.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).  
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**  
See Section 13 for disposal information.  
See Section 8 for information on personal protection equipment.

· **Protective Action Criteria for Chemicals**

· <b>PAC-1:</b>		
64-17-5	ethanol	1,800 ppm
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	120 mg/m <sup>3</sup>
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m <sup>3</sup>
111-30-8	glutaral	0.2 ppm
88-58-4	2,5-di-tert-butylhydroquinone	6.3 mg/m <sup>3</sup>
· <b>PAC-2:</b>		
64-17-5	ethanol	3300* ppm
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	1,300 mg/m <sup>3</sup>
868-77-9	2-hydroxyethyl methacrylate	21 mg/m <sup>3</sup>

(Contd. on page 4)



**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**

		(Contd. of page 3)
111-30-8	glutaral	1 ppm
88-58-4	2,5-di-tert-butylhydroquinone	69 mg/m <sup>3</sup>
<b>· PAC-3:</b>		
64-17-5	ethanol	15000* ppm
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	7,900 mg/m <sup>3</sup>
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m <sup>3</sup>
111-30-8	glutaral	5 ppm
88-58-4	2,5-di-tert-butylhydroquinone	110 mg/m <sup>3</sup>

**7 Handling and storage**

- **Handling**
  - **Precautions for safe handling**  
Keep receptacles tightly sealed.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
  - **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
  - **Storage**
    - **Requirements to be met by storerooms and receptacles:** No special requirements.
    - **Information about storage in one common storage facility:** Not required.
    - **Further information about storage conditions:** Keep cool, if possible (not above 25 °C).
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

<b>· Components with limit values that require monitoring at the workplace:</b>	
<b>64-17-5 ethanol</b>	
PEL	1900 mg/m <sup>3</sup> , 1000 ppm
REL	1900 mg/m <sup>3</sup> , 1000 ppm
TLV	1880 mg/m <sup>3</sup> , 1000 ppm
<b>111-30-8 glutaral</b>	
REL	Short-term value: C 0.8 mg/m <sup>3</sup> , C 0.2 ppm
TLV	Short-term value: C 0.2 mg/m <sup>3</sup> , C 0.05 ppm
	SEN
<b>112926-00-8 amorphous silica</b>	
PEL	Short-term value: 80 mg/m <sup>3</sup> as % SiO <sub>2</sub>
REL	6 mg/m <sup>3</sup>
TLV	10 mg/m <sup>3</sup> (e)

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)



**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**

(Contd. of page 4)

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

· **Breathing equipment:** Suitable respiratory protective device recommended.

· **Protection of hands:**

- If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.
- Solvent resistant gloves
- Check protective gloves prior to each use for their proper condition.
- recommended

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

- Butyl rubber, BR
- Nitrile rubber, NBR

· **Eye protection:** Tightly sealed goggles.

· **Body protection:** Light weight protective clothing

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- **Form:** Fluid
- **Color:** Yellowish
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

- **Melting point/Melting range:** undetermined
- **Boiling point/Boiling range:** undetermined

· **Flash point:** Not applicable

· **Flammability (solid, gaseous)** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 6)



**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**

(Contd. of page 5)

· <b>Explosion limits:</b>	
· Lower:	Not determined.
· Upper:	Not determined.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density at 20 °C (68 °F):</b>	1 g/cm <sup>3</sup> (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· <b>Solubility in / Miscibility with</b>	
· Water:	Not miscible or difficult to mix
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
· dynamic:	Not determined.
· kinematic:	Not determined.
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** none
- **Additional information:** -

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>64-17-5 ethanol</b>		
Oral	LD50	10470 mg/kg (rat) (OECD 401)
<b>72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazaheptadecane-1,16-diyl bismethacrylate</b>		
Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)
<b>868-77-9 2-hydroxyethyl methacrylate</b>		
Oral	LD50	5564 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (can)
<b>Poly(methacrylic-oligo-acrylic acid)</b>		
Oral	LD50	>5000 mg/kg (rat)
<b>70293-55-9 4-methacryloxyethyltrimellitic acid anhydride</b>		
Oral	LD50	>2000 mg/kg (mouse)
Dermal	LD50	>2000 mg/kg (mouse)

(Contd. on page 7)



**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**

(Contd. of page 6)

**111-30-8 glutaral**

Oral LD50 77 mg/kg (rat)

**· Primary irritant effect:**

- on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.

**· Sensitization:**

- Sensitization possible through inhalation.
- Sensitization possible through skin contact.

**· Additional toxicological information: Harmful**

**· Carcinogenic categories**

**· IARC (International Agency for Research on Cancer)**

64-17-5 ethanol

1

**· NTP (National Toxicology Program)**

None of the ingredients is listed.

**· OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**· Reproductive toxicity** Based on available data, the classification criteria are not met.

**12 Ecological information**

**· Toxicity**

**· Aquatic toxicity:**

**64-17-5 ethanol**

LC50/96h	14200 mg/l (fish)
ErC50 / 72 h	275 mg/l (algae) (OECD 201)
EC50/96h	129000 mg/L (fish)
LC50/48h	5012 mg/L (daphnia)
ErC10/72h	11.5 mg/L (algae) (OECD 201)
NOEC 5d	250 mg/L (fish) (OECD 212)
NOEC 10d	9.6 mg/L (daphnia)

**72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate**

EC50/48h	>1.2 mg/l (daphnia) (OECD 202)
LC50/96h	10.1 mg/l (fish) (OECD 203)
ErC50 / 72 h	>0.68 mg/l (algae) (OECD 201)
NOEC / 72h	0.21 mg/l (algae) (OECD 201)

**868-77-9 2-hydroxyethyl methacrylate**

EC50/48h	380 mg/l (daphnia)
LC50/96h	>100 mg/l (fish)
EC50	>3000 mg/l (bacteria)
NOEC / 21d	24.1 mg/l (daphnia)
ErC50 / 72 h	836 mg/l (algae)
NOEC / 72h	400 mg/l (algae) (OECD 201)

(Contd. on page 8)





**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**





(Contd. of page 7)

· <b>Persistence and degradability</b>	
<b>64-17-5 ethanol</b>	
biodegradability	84 % /20d (nd)
<b>72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate</b>	
biodegradability	22 % /28d (nd) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)
· <b>Behavior in environmental systems:</b>	
· <b>Bioaccumulative potential</b> No further relevant information available.	
· <b>Mobility in soil</b> No further relevant information available.	
· <b>Additional ecological information:</b>	
· <b>General notes:</b> Avoid transfer into the environment.	
· <b>Results of PBT and vPvB assessment</b>	
· <b>PBT:</b> Not applicable.	
· <b>vPvB:</b> Not applicable.	
· <b>Other adverse effects</b> No further relevant information available.	

**13 Disposal considerations**

- **Waste treatment methods**
  - **Recommendation**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
  - **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

· <b>UN-Number</b>	
· <b>DOT, ADR, IMDG, IATA</b>	UN1170
· <b>UN proper shipping name</b>	
· <b>DOT, IATA</b>	Ethanol
· <b>ADR</b>	1170 Ethanol
· <b>IMDG</b>	ETHANOL (ETHYL ALCOHOL)
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
<hr style="border-top: 1px dashed black;"/>	
· <b>ADR</b>	
	
· <b>Class</b>	3 (F1) Flammable liquids

(Contd. on page 9)





**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**

(Contd. of page 8)

· Label	3
· IMDG	
· Class	3 Flammable liquids
· Label	3
· IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	III
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No Yes (DOT) Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-D
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	-
· DOT	
· Remarks:	Special marking with the symbol (fish and tree).
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)



**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**

(Contd. of page 9)

· **UN "Model Regulation":** UN 1170 ETHANOL, 3, III

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

· **Sara**

· **SARA Section 355 (extremely hazardous substances)**

None of the ingredients is listed.

· **SARA Section 313 (specific toxic chemical listings)**

None of the ingredients is listed.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Prop 65 - Chemicals known to cause cancer**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5 ethanol

· **Carcinogen categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

64-17-5 ethanol

A3

111-30-8 glutaral

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapor.

H227 Combustible liquid.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 11)



**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 08/10/2021

Reviewed on 08/10/2021

**Trade name: iBOND Total Etch**

(Contd. of page 10)

*H335 May cause respiratory irritation.*

· **Date of preparation / last revision 08/10/2021 / 3**

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **\* Data compared to the previous version altered.**

US