



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/25/2019

Reviewed on 07/25/2019

1 Identification

· **Product identifier**

· **Trade name:** dima Print Stone beige

· **Application of the substance / the mixture** Manufacture of dental prothesis

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany) Tel.: +49 (0)800 4372522

· **Information department:**

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545

e-mail: customer.servicehka@kulzer-dental.com

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545

e-mail: customer.servicehka@kulzer-dental.com

· **Emergency telephone number:**

Emergency CONTACT (24-Hour-Number)

ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

· **Classification of the substance or mixture**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

(2,4,6-trioxo-1,3,5-triazinane-1,3,5-triyl)triethylene triacrylate

(octahydro-4,7-methano-1H-indenyl)methyl acrylate

Tricyclodecane dimethanol diacrylate

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

· **Hazard statements**

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

· **Precautionary statements**

Wash thoroughly after handling.

Avoid release to the environment.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/25/2019

Reviewed on 07/25/2019

Trade name: dima Print Stone beige

(Contd. of page 1)

- **Classification system**
- **NFPA ratings for USA (scale 0-4)**



- **HMS-Ratings (Scale 0-4)**

HEALTH	3	Health = *3
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** -

- **Dangerous components:**

40220-08-4	(2,4,6-trioxo-1,3,5-triazinane-1,3,5-triyl)triethylene triacrylate Eye Dam. 1, H318; Skin Sens. 1B, H317	10-25%
93962-84-6	(octahydro-4,7-methano-1H-indenyl)methyl acrylate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317; STOT SE 3, H335	10-25%
42594-17-2	Tricyclodecane dimethanol diacrylate Skin Sens. 1B, H317	10-25%
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide Skin Sens. 1, H317	0-5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **Information for doctor**
 - **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

US

(Contd. on page 3)



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/25/2019

Reviewed on 07/25/2019

Trade name: dima Print Stone beige

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
 - **Protective equipment:** No special measures required.
- **Additional information** -

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose of the collected material according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· PAC-1:		
13463-67-7	Titanium dioxide	30 mg/m ³
2530-85-0	3-trimethoxysilylpropyl methacrylate	71 mg/m ³
64-19-7	acetic acid	5 ppm
· PAC-2:		
13463-67-7	Titanium dioxide	330 mg/m ³
2530-85-0	3-trimethoxysilylpropyl methacrylate	780 mg/m ³
64-19-7	acetic acid	35 ppm
· PAC-3:		
13463-67-7	Titanium dioxide	2,000 mg/m ³
2530-85-0	3-trimethoxysilylpropyl methacrylate	4,700 mg/m ³
64-19-7	acetic acid	250 ppm

7 Handling and storage

- **Handling**
 - **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage**
 - **Requirements to be met by storerooms and receptacles:**
Protect from exposure to the light.

(Contd. on page 4)



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/25/2019

Reviewed on 07/25/2019

Trade name: dima Print Stone beige

(Contd. of page 3)

- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
 - **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
 - **Personal protective equipment**
 - **General protective and hygienic measures**
Avoid contact with the eyes.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
 - **Breathing equipment:** Not required.
 - **Protection of hands:**
If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.
Check protective gloves prior to each use for their proper condition.
recommended
 - **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
 - **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
Butyl rubber, BR
Nitrile rubber, NBR
 - **Eye protection:** Not absolutely necessary.
 - **Body protection:** Light weight protective clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
 - **General Information**
 - **Appearance:**
 - **Form:** Fluid
 - **Color:** Light brown
 - **Odor:** Petrol-like
 - **Odor threshold:** Not determined.
 - **pH-value:** Not determined.
 - **Change in condition**
 - **Melting point/Melting range:** undetermined

(Contd. on page 5)



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/25/2019

Reviewed on 07/25/2019

Trade name: dima Print Stone beige

(Contd. of page 4)

· Boiling point/Boiling range:	undetermined
· Flash point:	Not applicable
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	ca. 1 g/cm ³ (~8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· dynamic:	Not determined.
· kinematic:	Not determined.
· Solvent content:	
· Water:	0,0 %
· Solids content:	0,3 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Possibility of hazardous reactions**
 - Photoreactive
 - Polymerization
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** none
- **Additional information:** -

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

41137-60-4 diurethandimethacrylate

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

(Contd. on page 6)



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/25/2019

Reviewed on 07/25/2019

Trade name: dima Print Stone beige

(Contd. of page 5)

42594-17-2 Tricyclodecane dimethanol diacrylate

Oral LD50 >2,000 mg/kg (rat) (OECD 439)

Dermal LD50 >2,000 mg/kg (rat) (OECD 437)

162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

· Primary irritant effect:

· **on the eye:** Strong irritant with the danger of severe eye injury.

· **Sensitization:** Sensitization possible through skin contact.

· Additional toxicological information:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

13463-67-7 Titanium dioxide

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

42594-17-2 Tricyclodecane dimethanol diacrylate

EC50/48h 2.36 mg/l (daphnia) (OECD 202)

LC50/96h 1.65 mg/l (fish) (OECD 203)

ErC50 / 72 h 1.6 mg/l (algae) (OECD 201)

162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

EC50/72h >0.26 mg/l (algae) (OECD 201)

EC50/48h >1.175 mg/l (daphnia) (OECD 202)

LC50/96h >0.09 mg/l (fish) (OESO 203)

· **Persistence and degradability** No further relevant information available.

· Behavior in environmental systems:

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· Ecotoxicological effects:

· **Remark:** Harmful to fish

· Additional ecological information:

· **General notes:** Harmful to aquatic organisms

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· **Recommendation** Smaller quantities can be disposed of with household waste.

(Contd. on page 7)



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/25/2019

Reviewed on 07/25/2019

Trade name: dima Print Stone beige

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	Void
· DOT, ADR, ADN, IMDG, IATA	
· UN proper shipping name	Void
· DOT, ADR, ADN, IMDG, IATA	
· Transport hazard class(es)	Void
· DOT, ADR, ADN, IMDG, IATA	
· Class	
· Packing group	Void
· DOT, ADR, IMDG, IATA	
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	-
· UN "Model Regulation":	Void

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara
· SARA Section 355 (extremely hazardous substances)
None of the ingredients is listed.
· SARA Section 313 (specific toxic chemical listings)
None of the ingredients is listed.
· Proposition 65
· Prop 65 - Chemicals known to cause cancer
13463-67-7 Titanium dioxide
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
· Chemicals known to cause developmental toxicity:
None of the ingredients is listed.
· Carcinogenicity categories
· EPA (Environmental Protection Agency)
None of the ingredients is listed.

(Contd. on page 8)



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/25/2019

Reviewed on 07/25/2019

Trade name: dima Print Stone beige

(Contd. of page 7)

· TLV (Threshold Limit Value established by ACGIH)	
13463-67-7 Titanium dioxide	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7 Titanium dioxide	

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

· **Date of preparation / last revision** 07/25/2019 / -

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1B: Skin sensitisation – Category 1B
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**